

Algefjerner

Application

Professional outdoor algae remover. The product is used for controlling algae on clay and concrete roofs, wood, tiles, and masonry. May only be used for professional algae control.

Apply the product using a low-pressure sprayer (< 10 bar), sprayer, brush, or broom. Ensure that the entire surface is saturated and that the whole area is treated at the same time.

Consider wind direction and ensure that any residues are collected and disposed of correctly. The product should not be rinsed off after application.

The deposits will gradually disappear due to the product's effect and natural weather conditions.

When the surface appears dry, any subsequent treatment may be carried out. Treatment is performed 1–2 times per year, or as needed.

The product must not be used near surface water or in areas where there is a risk of direct discharge into surface water.

When used on roof:

The working solution must be collected after application, for example via the gutter, and must not be discharged into the sewer system.

When used on vertical surfaces:

The soil around the treated area must be covered for at least 0.5 meters so that spills and runoff near the surface can be collected and disposed of. The working solution must not be discharged into the sewer system.

The product may only be used if the weather forecast predicts no rain for 24 hours after treatment. The working solution must be prepared on a solid, impermeable surface. Avoid release into the environment. Do not empty into drains.

Keep locked up and out of reach of children. Do not store near food, beverages, or animal feed. The container must not be reused.

Dosage

The algae remover must be diluted before use. 25 kg container of working solution:

1.37 L product + 23.63 L water

1 L of working solution (diluted product) is sufficient for treating approx. 10–20 m²

About us

At Interfiller, we work closely with our suppliers, partners and customers to create quality products with results. For almost 50 years, Interfiller A/S has built a solid company that today produces Danish products for both horticulture and agriculture.

At Interfiller, we take pride in in-depth knowledge about the products we sell and their practical application. Chelated micronutrients ensure reduced fertilizer consumption and enable agriculture and horticulture to increase yields and improve product quality while reducing environmental impact.

Through our products, production processes and services, we work together with our customers, employees and strategic partners to contribute to a global impact that helps secure our common future.

Contact us



+45 56 66 13 66



kontakt@interfiller.dk



www.interfiller.com

Follow us

Follow us on social media where we share current knowledge about our products and our latest projects. .

